



**TECHNICAL DATA**

Order no.	82995.2
Certified to	EN 14055
matching for	Floorstanding WC pan order no. 82595.1, 82595.2, 82595.8 / Charge 000, 82596.2 / Charge 000, 82596.4
Specification	Flushing mechanism Dual-Flush With water condensation insulation: Charge 872 – 5/3-l (6/3-l-flush, 4,5/3-l-flush) Without water condensation insulation: Charge 876 – 5/3-l (6/3-l-flush, 4,5/3-l-flush)
Water inlet	side left, side right, 3/8" brass
Weight	13,0 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	Angle valve for water inlet Water inlet hose
Colours	see colour table

**SPECIFICATION TEXT**

Cistern LAUFEN PRO, sanitary ceramic  
EN 14055  
dimensions 375 x 160 x 395 mm  
Dual-Flush 5/3-l (6/3-l-flush, 4,5/3-l-flush)  
water inlet side left, side right, 3/8" brass  
matching floorstanding WC pan, order no. 82595.1/option 000,  
82595.2, 82595.8/option 000, 82596.2/option 000, 82596.4  
Special feature: with or without water condensation insulation  
Order no. 82995.2

**TECHNICAL DRAWINGS / S 1 : 20**

