

Elmasonic S 130 H

Ultrasonic cleaning unit

Elma Order Nos.

Elmasonic S 130 H (220-240 V)	100 9539
Stainless steel tray holder for semi-tray cassettes	100 9782
Basket stainless steel	100 9783
Basket stainless steel ½ size	100 9786
Cover stainless steel	101 0085
Cover stainless steel ½ size	103 1451
Stainless steel cover with hole for one beaker	103 1429
Glass beaker 1000 ml	207 035 0000
Further accessories on request	



S 130 H

Specifically designed and suitable for cleaning of semi-tray cassettes with max. dimensions of 140 x 205 x 45 mm or for simultaneous use of one beaker and one basket for cleaning instruments. State-of-the art microprocessor controlled ultrasonic cleaning and sweep technology. The user-friendly LED-display ensures an excellent operation. Further advantages:

- high-performance 37 kHz sandwich transducer systems
- cleaning tank made of cavitation-resistant stainless steel
- user-friendly and clear operating panel, splash water proof
- LED-Display showing set and remaining time of cleaning period
- Turning knob for setting continued and short-period operation from 1 to 30 min
- temperature-controlled ultrasonic operation
- sweep function for an optimised sound field distribution in the cleaning liquid by frequency modulation
- degas function for the efficient degassing of the cleaning liquid and for laboratory purposes
- auto degas function for automatic degassing cycles, i.e. with fresh cleaning liquids
- dry-run protected heating
- Turning knob temperature. Temperature range variable in 5°C steps from 30° up to 80°C
- LED-Display for pre-set and actual temperature
- plug-in mains supply
- ergonomically shaped plastic handles
- Turning knob for tank drainage at side of unit for simple get effective draining of tank

Technical data

Mains voltage (Vac)	220-240 V	Weight (kg)	8.0
Max. filling volume tank (lit.)	12.5	Material tank	stainless steel
Ultrasonic frequency (kHz)	37	Material casing	stainless steel
Power consumption total (W)	1100	Drain	3/8"
Ultrasonic power effective (W)	300	Carrying handles (plastic)	√
Ultrasonic peak performance max.*(W)	1200	CE-compliant	√
Heating power (W)	800	Protection class	IP 20
Unit outer dimensions W / D / H (mm)	400 / 275 / 295		
Tank internal dimensions W / D / H (mm)	325 / 225 / 175		
Basket internal dimensions W/D/H (mm)	296 / 200 / 75		

* S 10 – S 15 H: impulse wave form; S 30 – S 900 H: standard sine-wave modulation
The choice of the waveform has been matched to the relevant tank size. The signal form of the wave results in a factor 4 or 8 for the ultrasonic peak max., depending on the modulation of the wave.