



## Refrigerated counter for the 'Pastry' world DOLCE Range

### Range plus:

- \* AISI 304 Stainless steel top, 15/10 mm thickness
- \* Soundproofing, water-repellent, flame retardant panel
- \* Ergonomy and design



<b>Commercial code</b>	<b>KBS16A</b>
<b>Temperature range</b>	-2/+8° C
<b>Technical features</b>	<p>Exterior/interior: all-in-one insulated structure AISI 304 stainless steel, suitable to pastry containers 60x40 cm (h 4 cm). Doors, side panels and control panel with Scotchbrite finish. Polyurethane insulation: 60 mm thick, density 40 kg/m<sup>3</sup>. Automatic evaporation of condense drain. CE Mark.</p> <p>Refrigerant capacity: 475 W at evaporation temperature of -10°C. Ventilated refrigerating system with protected finned evaporator and electric fans. Frontal air circulation in motor compartment to allow any positioning option while assuring peak motor unit reliability. Refrigerant gas R404a. Temperature range -2/+8°C even at a room temperature of +43°C (climate class "T"). Automatic defrosting and evaporation of the condense drain. Noise level &lt;70 dBA.</p>
<b>Functional features</b>	<p>All-in-one structure in st/steel AISI 304 with an insulating thickness of 60 mm; the insulation is ensured by the injection of high-density CFC-free polyurethane foam. Worktop, 50 mm high, made in AISI 304 stainless steel, 15/10 thick, rounded on the front side with 8,5 cm high rear-splashback. Worktop featuring inside a water and fire-proof panel. Control panel with digital thermometer-thermostat and relative humidity setting device, range 75 - 90%. Refrigerated compartment with 2 doors. Gross capacity: 383 liters. Isolated doors equipped with removable magnetic gasket assuring an optimum closing. Self-closing system. Stainless steel handles. Depth with door open 125,5 cm.</p> <p>Drain hole to ease cleaning operations of the compartment. Easy removable AISI 304 stainless steel racks to support containers. Standard equipment, each refrigerated compartment: 7 couples of stainless steel runners useful for pastry containers 60x40 cm (4 cm h). Adjustable AISI 304 stainless steel feet.</p>
<b>External dimensions</b>	length 160 x 80 depth x 96,5 high cm
<b>Electric power</b>	Kw 0,55 - Standard voltage: V-Hz 230V 1N-/50Hz
<b>Volume/ Net weight</b>	M3: 1,23 Kg: 133