

VITALITY

The ideal boost for your offer







TECHNICAL SPECIFICATIONS

- Electrical supply: 220-240V; 50/60HZ
- Internal electrical supply: 0.65 kW
- Food management: preset for preservation of perishable food products as equipped with refrigerator group that can guarantee 3°C in the three lower drawers. Health control safety device available on the last two drawers and when the electronic sensor detect a temperature above the established safety temperature for perishable food products all food sales will be inhibited.
- The easily accessible and removable refrigeration unit. The dust filter is easy to extract, making maintenance easier.
- Refrigerant gas: R 290, gas capacity 100g

FEATURES

- 6 drawers, 8 spirals.
- Supplied with a kit including 8 products holders.
- Dispenser insulation made using a material with a high thermal
- · Large window illuminated by white LED bars, and made with lowemission magnetron-coated glass, enabling the products to be displayed optimally.
- Window with anti-condensation resistance.
- Door with large surface area that can be customised with stickers and black-coated aluminium frame.
- Dispensing compartment without transparent window.
- Adjustable tray layout: 7.5 mm pitch between the fixing holes of the

tray guides for a more flexible internal configuration.

- Anti-theft product delivery door "push".
- Version with electronic tags for displaying prices.

MASTER VERSION

- Illuminated alphanumeric selection keypad with 12 push buttons.
- Wide 3.5" TFT LCD customisable colour display.
- Refund coin introduction and refund system standard.

SLAVE VERSION

- Slave version works together with a single hot drinks or snack&food master machine, with a single payment system.
- Alphanumeric keypad selection is on the master machine.

ACCESSORIES

• Sandwich tray kit (7 selections).

PAYMENT SYSTEM


• Compatible with all main payment systems based on Executive and MDB protocols.

ENVIRONMENT

- Energy Saving Mode: management of the Led lighting on/off, during specified time slots.
- Product drawer made of 50% recycled plastic (on SLAVE model).
- In compliance with ROHS and WEEE.

MODEL VITALITY	VITALITY L 6-44 MA	VITALITY L 6-44 MA DISP	VITALITY L 6-44 SL
Version	master	master	slave
Alphanumeric selection keypad	•	•	-
Electronic tags	-	•	-
Selections/capacity	44/356	44/356	44/356
Drawers/spirals	6/8	6/8	6/8
Products drop sensor	•	•	•
■ Energy class	D		TBD
Dimensions mm	1830H × 870W × 800D	1830H x 870W x 800D	1830H x 720W x 800D
Weight	243 KG	243 KG	202 KG

VITALITY MASTER / SLAVE
























RECYCLED MATERIAL





REFRIGERATION













